

Kompaktes Mikrofon für Kameras und Smartphones

- Multikompatibel: Geeignet für Kameras, Smartphones und Tablets via mitgeliefertem TRS-, TRRS- und USB-C-Kabel
- Kristallklarer Ton: Nierencharakteristik für gerichtete, professionelle Sprachaufnahmen
- Keine Störgeräusche: Anti-Schock-Halterung, Popschutz und Windschutz gegen unerwünschte Vibrationsgeräusche, Plosivlaute und Umgebungsgeräusche
- Plug and Play: Sofort einsatzbereit ohne App oder Installation
- Keine Batterie nötig: Stromversorgung direkt über das angeschlossene Gerät
- Einfache Montage: Praktische und sichere Befestigung via Cold-Shoe-Anschluss auf Kamera, Stativ oder Selfie Stick
- Kompakt und leicht: Perfekt für mobile Einsätze



Kamera und Smartphone nicht im Lieferumfang enthalten.

Technische Daten

Wandler	Kondensator
Richtcharakteristik	Niere
Ausgangsimpedanz	1,19 k Ω (f = 1.000 Hz, Pin = 1 Pa)
Frequenzgang	100 – 20.000 Hz $\pm$ 3 dB
Signal-Rausch-Abstand	> 60 dB
Max. Schalldruckpegel (SPL)	104 dB (1.000 Hz, 3 % THD)
Empfindlichkeit	-35 dB $\pm$ 1/-2 dB (f = 1.000 Hz, Pin = 1 Pa)
Gesamte harmonische Verzerrung (THD)	< 3 % (f = 1.000 Hz, Pin = 104 dB SPL)
Einsprechrichtung	End (frontal)
Stromversorgung	Plug-in: Betriebsspannung 1,1 – 10,0 V, Nennspannung 1,5 V
Anschluss	Klinken-Anschluss 3,5 mm, 1/4-Zoll-Anschluss, Cold-Shoe-Anschluss
Betriebstemperatur	-25 – 70 °C
Maße	2,2 x 2,2 x 7,2 cm
Gewicht	35 g

Lieferumfang und Verpackungsdetails

Lieferumfang	Mikrofon, TRS-Kabel, TRRS-Kabel, USB-C-Kabel, Anti-Schock-Halterung, Popschutz, Windschutz, 2x Ersatz-Ringe, Tasche, Bedienungsanleitung
Verpackungsmaße -Gewicht	18,8 x 13,1 x 5,1 cm 230 g

Änderungen von Design und technischen Daten bleiben vorbehalten und bedürfen keiner Ankündigung.

Compact Microphone for Cameras and Smartphones

- Multi-compatible: Suitable for cameras, smartphones and tablets via included TRS, TRRS and USB-C cable
- Crystal clear sound: Cardioid polar pattern for directional, professional voice pickup
- No noise: Anti-shock mount, pop filter and windscreen against unwanted vibration noise, plosives and ambient noise
- Plug and Play: Ready to use right out of the box without an app or installation
- No battery required: Power supply directly from the connected device
- Easy mounting: Practical and secure attachment via cold-shoe connection to camera, tripod or selfie stick
- Compact and lightweight: Perfect for mobile use



Camera and smartphone not included.

Technical Data

Transducer	Condenser
Polar pattern	Cardioid
Output impedance	1.19 kΩ (f = 1,000 Hz, Pin = 1 Pa)
Frequency response	100 – 20.000 Hz ± 3 dB
Signal-to-noise ratio	> 60 dB
Max. sound pressure level (SPL)	104 dB (1,000 Hz, 3 % THD)
Sensitivity	–35 dB +1/–2 dB (f = 1,000 Hz, Pin = 1 Pa)
Total harmonic distortion (THD)	< 3 % (f = 1,000 Hz, Pin = 104 dB SPL)
Speaking direction	End (frontal)
Power supply	Plug-in: Operating voltage 1.1 – 10.0 V, nominal voltage 1.5 V
Connection	Jack connection 3.5 mm, 1/4-inch connection, cold-shoe connection
Operating Temperature	–25 – 70 °C
Dimensions	2.2 x 2.2 x 7.2 cm
Weight	35 g

What's in the Box and Packaging Details

What's in the box	Microphone, TRS cable, TRRS cable, USB-C cable, anti shock mount, pop filter, windscreen, 2x replacement rings, bag, user manual
Packaging Dimensions Weight	18.8 x 13.1 x 5.1 cm 230 g

Design and technical data are subject to change without notice.