

Datenblatt Art. 388.471

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

SMART

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung Frequenz	16A / 250V~ 50 Hz	Rated current / rated voltage Frequency	16A / 250V~ 50 Hz
Netzanschluss		Power supply	
Zuleitung Wiederanschließbar	3,0m H05VV-F 3G1,50mm²	Supply cable rewireable	3,0m H05VV-F 3G1,50mm²
Stecker Steckertyp	CEE 7/7 (Type E/F) Winkelstecker	Plug Plug type	CEE 7/7 (Type E/F) right angled plug
Stromausgang		Power output	
Steckdosen 3x CEE 7/3 (Type F) 2-polig mit Schutzkontakt Mit erhöhtem Berührungsschutz braun, 35°, 16A / 250V~, IP20		Socket outlets 3x CEE 7/3 (Type F) 2-pole with earthing contact With shutter brown, 35°, 16A / 250V~, IP20	
Weitere Produkteigenschaften		Further product attributes	
Material Gehäuse: Polypropylen, 850°C, braun		Material Housing: Polypropylene, 850°C, brown	
Lieferumfang 1x Steckdosenleiste SMART Im Polybeutel mit BACHMANN header		Scope of delivery 1x Power strip SMART In polybag with BACHMANN header	
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP20	Protection type	IP20
Konformität / Approbation		Conformity / Approval	
Bauart geprüft	IEC 60884, VDE 0620- 1	Type approved	IEC 60884, VDE 0620- 1

