

		1	2	3	4	5	6	7	8	9	10	11	12	13	14		
A	Pin-Belegung / Pin Assignment		Art.-Nr. / Item No.		Beschreibung / Description		Länge / Length (L)		AD / OD		Innenleiter Material / Material inner conductor						A
			41081		HDMI 2.1 Kabel 0050 0,5m STD sw		500 ± 20 mm		6.0 ± 0.15 mm		(1/0.254 x 1P + D (1/0.254) + AM + M) x 5 PCS + 1/0.254 x 4C + AM + D (1/0.254) + B (64/0.12ALM)						
B			41082		HDMI 2.1 Kabel 0100 1,0m STD sw		1000 ± 30 mm		6.0 ± 0.15 mm		(1/0.254 x 1P + D (1/0.254) + AM + M) x 5 PCS + 1/0.254 x 4C + AM + D (1/0.254) + B (64/0.12ALM)						B
			41083		HDMI 2.1 Kabel 0150 1,5m STD sw		1500 ± 50 mm		6.0 ± 0.15 mm		(1/0.254 x 1P + D (1/0.254) + AM + M) x 5 PCS + 1/0.254 x 4C + AM + D (1/0.254) + B (64/0.12ALM)						
C			41084		HDMI 2.1 Kabel 0200 2,0m STD sw		2000 ± 50 mm		6.0 ± 0.15 mm		(1/0.254 x 1P + D (1/0.254) + AM + M) x 5 PCS + 1/0.254 x 4C + AM + D (1/0.254) + B (64/0.12ALM)						C
			47575		HDMI 2.1 Kabel 0300 3,0m STD sw		3000 ± 50 mm		7.3 ± 0.15 mm		(7/0.12BC x 1P + 1/0.25TC + AM + M) x 5 PCS + 7/0.12BC x 4C + AM 1/0.25TC + 128/0.12ALM						
D			52766		HDMI 2.1 Kabel 0500 5,0m STD sw		5000 ± 70 mm		7.8 ± 0.2 mm		(1/0.40 x 1P + D (1/0.32) + AM +HM) x 5 PCS + 1/0.40 x 4C + AM + D (1/0.40) + B (128/0.12ALM)						D
E																	E
F																	F
G																	G
H																	H
I																	I
J																	J

P1		P2	
1	1	1	1
3	3	3	3
2	2	2	2
4	4	4	4
6	6	6	6
5	5	5	5
7	7	7	7
9	9	9	9
8	8	8	8
10	10	10	10
12	12	12	12
11	11	11	11
13	13	13	13
15	15	15	15
16	16	16	16
14	14	14	14
19	19	19	19
17	17	17	17
18	18	18	18
SHELL DRAIN SHELL			

P1		P2	
2	1	2	1
18	19	18	19

L	
8.8 mm (min.)	
8.8 mm (min.)	

Ultra High Speed HDMI™ Kabel		Ultra High Speed HDMI™ Cable	
- max. Datenrate 48 Gbit/s		- max. Data rate 48 Gbit/s	
- Hochgeschwindigkeitskabel für 8K @ 60 Hz		- High speed cable for 8K @ 60 Hz	
- Anschlüsse: 2x HDMI™-Stecker (Typ A)		- Connectors: 2x HDMI™ plug (Type A)	
- Kontakte: vergoldet		- Contacts: gold-plated	
- Anzahl Schirmungen: 2 (Aluminiumgeflecht 144x)		- Number of shieldings: 2 (aluminum braiding 144x)	
- Material Gehäuse: PVC		- Material housing: PVC	
- Material Kabelmantel: PVC		- Material cable jacket: PVC	
- Isolationswiderstand: 10 MΩ min.		- Insulation resistance: 10 MΩ min.	
- Kontaktwiderstand: 5 Ω max.		- Contact resistance: 5 Ω max.	
- Max. Auflösung: 4K Ultra HD 2160p (120 Hz), 8K Ultra HD 4320p (60 Hz)		- Max. Resolution: 4K Ultra HD 2160p (120 Hz), 8K Ultra HD 4320p (60 Hz)	
- Unterstützte Standards: HDR (High Dynamic Range), HDCP 2.2, HDMI™ Ethernet Channel (HEC), 4K 3D, 21:9 Cinemascope, Consumer Electronics Control (CEC) Enhanced Audio Return Channel (eARC)		- Supported standards: HDR (High Dynamic Range), HDCP 2.2, HDMI™ Ethernet Channel (HEC), 4K 3D, 21:9 Cinemascope, Consumer Electronics Control (CEC) Enhanced Audio Return Channel (eARC)	
- Konformität: RoHS		- Conformity: RoHS	

Änderungen		Datum		Name		Bezeichnung		Blatt	
Datum		Name		gez.: 01.02.2021 aw		HDMI 2.1 Kabel XXXX Xm STD sw goobay®		1/1	
				gepr.: 01.02.2021 aw					
				Norm:		Zeichnungs-Nr.:		von	
				Änderungen vorbehalten / Subject to change					