



WORK CLEVER. CLICK TOGETHER.

i-BOXX Rack 3er Block i-BOXX Rack 3-pieces



PRODUKTDATENBLATT | PRODUCT DATA SHEET

L-BOXX
BASELINE

Allgemeine Daten

Bezeichnung i-BOXX Rack 3er Block

Artikelnummer 6100000338

GTIN/EAN 4045294846206

Zolltarifnummer 39269097



Ursprungsland Polen

Produktabbildung



Produktbeschreibung

- **Maximale Modularität**
Regalähnliches Aufnahmesystem für 3 i-BOXXen oder LS-Trays – unbegrenzt kombinier- und erweiterbar
- **Patentierte Klickverbindung**
Robuster Klickmechanismus für stabile Stapelverbindung und Tragen im Verbund
- **Optimale Organisation**
Ordnung und Übersicht durch strukturierte Aufbewahrungslösung im praktischen 3er-Block
- **Systemfähig**
Kompatibel mit dem gesamten L-BOXX System
- **Für mobile Anwendungen optimiert**
Integrierbar in Fahrzeugeinrichtungen namhafter Hersteller für einen sicheren Transport



Revision 5.0_2025-07

Farbe / Material

Farbe

RAL 9017 Verkehrsschwarz

RAL 7016 Anthrazitgrau

Material

- | | |
|-----------------|-----|
| ① i-BOXX Rack | ABS |
| ② i-BOXX Deckel | ABS |
| ③ Tragegriff | ABS |
| ④ Griffschale | ABS |
| ⑤ Koppelhebel | PA6 |



i-BOXX und LS-Tray sind nicht
im Lieferumfang enthalten

Technische Daten

Außenmaße

Breite	445 mm
Tiefe	342 mm
Höhe	305 mm

Innenmaße

Breite	355 mm
Tiefe	315 mm
Höhe (pro Rack)	79 mm

Eigengewicht 4,3 kg

Belastbarkeit Deckel 100 kg

Beladungskapazität
(pro Rack) 5 kg

Traglast Tragegriff 40 kg

Spritzwassergeschützt nein

Temperaturbereich -20°C bis +80°C

Zertifikate REACH (EG 1907/2006)

Kompatibel mit

- L-BOXXen
- LS-BOXX
- i-BOXX Rack
- i-BOXX
- LS-Tray
- L-BOXX Contractor



General Information

Product name i-BOXX Rack 3-pieces

Item no. 6100000338

GTIN/EAN 4045294846206

Customs tariff no. 39269097

Country of origin Poland

Product Image



Characteristics

- **Maximum Modularity**
Shelf-like storage system for 3 i-BOXXes or LS-Trays – infinitely combinable and expandable
- **Patented Click Connection**
Robust click mechanism for stable stacking and secure transport as a connected unit
- **Optimal Organization**
Structured storage solution in a practical 3-piece block for order and clarity
- **System Compatible**
Compatible with the entire L-BOXX system
- **Optimized for Mobile Use**
Integrates into vehicle equipment systems from leading manufacturers for safe transport



Revision 5.0_2025-07

Colour / Material

Colour RAL 9017 traffic black
RAL 7016 anthracit grey

Material

- ① i-BOXX Rack ABS
- ② i-BOXX Rack Deckel ABS
- ③ Top handle ABS
- ④ Grip handle ABS

- ⑤ Coupling latches PA6



i-BOXX and LS-Tray are not included
in the scope of delivery

Technical Data

External dimensions

Width	445 mm
Depth	342 mm
Height	305 mm

Internal dimensions

Width	355 mm
Depth	315 mm
Height (per Rack)	79 mm

Weight 4,3 kg

Load capacity lid up to 100 kg

Loading capacity max.
(per Rack) 5 kg

Load capacity top handle 40 kg

Splash-proof no

Temperature range -20°C till +80°C

Certificates REACH-(EG1907/2006)

Compatible with

- L-BOXXes
- LS-BOXX
- i-BOXX Rack
- i-BOXX
- LS-Tray
- L-BOXX Contractor

