

# TRUCKSTAR PRO H7

Brightest OSRAM truck halogen light



#### Up to 2.5 times longer lifetime

Reduced downtime and fleet costs compared to standard lamps



#### Up to 120% more brightness

More light allows to see farther and therefore react sooner compared to the minimum legal standard



#### Very high vibration resistance

Suitable for heavy duty applications



#### The most powerful halogen and signal truck lamps from OSRAM

Discover TRUCKSTAR PRO - the brightest halogen and signal truck lamps from OSRAM with excellent value for money. With extremely long life, up to 120% more light than standard lamps and very high vibration resistance these 24 volt lamps are ideal for professional drivers while reducing downtime and fleet costs. Thanks to the high vibration resistance, TRUCKSTAR PRO lamps are suitable even for heavy duty applications. Due to their impressive brightness and up to 2.5 times longer lifetime compared to standard lamps, the lamps improve your safety while driving on the road.

Technical data

Product information

|                                             |                        |
|---------------------------------------------|------------------------|
| Order reference                             | 64215TSP               |
| Application (Category and Product specific) | Halogen headlight lamp |

Electrical data


|                 |                    |
|-----------------|--------------------|
| Power input     | 75 W <sup>1)</sup> |
| Nominal voltage | 24.0 V             |
| Nominal wattage | 70.00 W            |
| Test voltage    | 28.0 V             |

<sup>1)</sup> Maximum

Photometrical data

|                         |         |
|-------------------------|---------|
| Luminous flux           | 1750 lm |
| Luminous flux tolerance | ±10 %   |

Dimensions & weight



|                |         |
|----------------|---------|
| Length         | 59.0 mm |
| Diameter       | 12.0 mm |
| Product weight | 12.50 g |

Lifespan

|             |        |
|-------------|--------|
| Lifespan B3 | 500 h  |
| Lifespan Tc | 1000 h |

Additional product data

|                             |       |
|-----------------------------|-------|
| Base (standard designation) | PX26d |
|-----------------------------|-------|

Product datasheet

Capabilities

|            |     |
|------------|-----|
| Technology | HAL |
|------------|-----|

Certificates & standards

|              |    |
|--------------|----|
| ECE category | H7 |
|--------------|----|

Country specific categorizations

|                 |          |
|-----------------|----------|
| Order reference | 64215TSP |
|-----------------|----------|

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                                                                                                                                                                               |
|-----------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Date of Declaration                                                   | 15-09-2023                                                                                                                                                                                    |
| Primary Article Identifier                                            | 4008321785091   4008321785114   4008321855954   4008321855978   4008321855930   4052899413818   4052899414013   4052899413917   4052899476042   4062172150521   4062172150453   4062172387637 |
| Candidate List Substance 1                                            | No declarable substances contained                                                                                                                                                            |
| Declaration No. in SCIP database                                      | In work                                                                                                                                                                                       |

Logistical Data

| Product code  | Product description | Packaging unit<br>(Pieces/Unit) | Dimensions (length<br>x width x height) | Volume               | Gross weight |
|---------------|---------------------|---------------------------------|-----------------------------------------|----------------------|--------------|
| 4008321785114 | TRUCKSTAR PRO H7    | Folding carton box<br>1         | 34 mm x 34 mm x<br>58 mm                | 0.07 dm <sup>3</sup> | 16.00 g      |
| 4008321785121 | TRUCKSTAR PRO H7    | Bundle<br>10                    | 69 mm x 58 mm x<br>172 mm               | 0.69 dm <sup>3</sup> | 155.00 g     |
| 4008321785138 | TRUCKSTAR PRO H7    | Shipping carton box<br>100      | 356 mm x 129 mm x<br>186 mm             | 8.54 dm <sup>3</sup> | 1727.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File                                                                                |                                               |
|-------------------------------------------------------------------------------------|-----------------------------------------------|
|  | 360 Degree Image<br>TRUCKSTAR PRO H7 64215TSP |

Product datasheet

**Legal advice**

Light output compared to the minimum ECE R112 requirements

**Application advice**

For more detailed application information and graphics please see product datasheet.

**Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

