

PERFORMANCE

Display Size	34"
View Area	799.8x334.8 mm
Panel	In-Plane Switching
Backlight	WLED
Aspect Ratio	21:9
Resolution	3440x1440
Pixel Pitch	0.2325x0.2325 mm
Dot / Pixel Per Inch	110 dpi
View Angle (H / V)	178° / 178°
Response Time	4ms GtG (Extreme mode) / 6ms GtG (Typical mode)
Color Support	1.07 Billion
Refresh Rate	24Hz - 120Hz
Brightness	350 cd/m ²
Contrast Ratio	2000:1
Color Gamut	98% DCI-P3, 99% sRGB
Screen Surface Treatment	Anti-glare
Curvature	3800R
Camera	Modular Camera Support
Microphone	None
Speakers	3Wx2, Optional Soundbar Support
Power Consumption (Typical / Maximum)	28W / 250W
Power Adapter	Integrated
Touchscreen	None

Smart System	None
DESIGN	
Stand	Tilt, Swivel, Height Adjust Stand
Case Color	Eclipse Black
Side Bezel Width	2.0 mm
Mounting	Supports VESA mount 100mm
ThinkCentre® M Series Support	Tiny Support
Pen	None

Dimensions (WxDxH)^[1]	- Lowest Position 817.1 x 220.0 x 393.8 mm (32.17 x 8.66 x 15.50 inches) - Highest Position 817.1 x 220.0 x 548.8 mm (32.17 x 8.66 x 21.61 inches) - Head Only 817.1 x 82.2 x 358.6 mm (32.17 x 3.24 x 14.12 inches)
Packaging Dimensions (WxDxH)	905.0 x 174.0 x 470.0 mm (35.63 x 6.85 x 18.50 inches)
Weight^[2]	- Monitor With Stand 10.0 kg (22.0 lbs) - Monitor Head Only 7.2 kg (15.9 lbs)

Packaging Weight	14.7 kg (32.4 lbs)
-------------------------	--------------------

CONNECTIVITY

USB Port	5x USB-A (USB 5Gbps, downstream), 2x USB-C® (USB 5Gbps, downstream), 1x USB-C® (USB 5Gbps, DP 1.4 Alt Mode HBR3, upstream), 1x USB-B (USB 5Gbps, upstream)
Video Connector	1x HDMI® 2.1 TMDS, 1x DP 1.4 (HBR3), 1x DP Out, 1x USB-C® (DP 1.4 Alt Mode HBR3)
Network Connectivity	1x RJ45, Ethernet (10M/100M/1000M/2500M)

SERVICE

Base Warranty	3-year
----------------------	--------

CERTIFICATIONS

Environmental Certification	ENERGY STAR® Certified, TCO 10, TCO Edge 2.1, EPEAT™ Gold
Ergonomic Certification	Eyesafe® Display 2.0, TÜV Low Blue Light (Hardware solution), TÜV Rheinland® IPS Black, TÜV Rheinland® Eye Comfort (5 Stars)
Sync Technology	None
Special Features	- HDR10 Compliance - Factory Calibration: Avg. Delta E<2 (for DCI-P3 and sRGB) - Picture In Picture (PIP) / Picture By Picture (PBP) Support - Lenovo® ThinkColour (Lenovo® Accessories and Display Manager) Support Lenovo® ThinkColour supports Windows® 10 & 11, Mac OS (functions vary across systems). Lenovo® Accessories and Display Manager is formerly Lenovo® Display Control Center. - AI Power Saving - KVM Switch (with eKVM) - LDFM (Lenovo® Display Fleet Manager) - Mirrored Power Button - Multi-sync - Natural Low Blue Light - Smart Power The Smart Power function intelligently detects overall power consumption and dynamically manages the power delivery to each device - Smart Sensor (Auto Ambient Brightness Sensor) - True Split

SOFTWARE

Operating System	Support Windows® 10, Windows® 11
-------------------------	----------------------------------

ACCESSORIES

Video Cables	DP cable, USB-B to USB-A cable, USB-C® to USB-C® cable
---------------------	--

MODEL

Announce Date	: 2025-04-24	Region	: EMEA
EAN / UPC / JAN	: 0198156243645 / 198156243645 / None		

· Lenovo reserves the right to change specifications without notice.
To see more note information, please access the [web page](#).