



PIN-Zuordnung | *PIN Assignment*

P1		P2
1	weiß/links | *white/left*	1
2	rot/rechts | *red/right*	2
3	Erdung | *drain*	3

Artikel-Nr. | *Item no.*	Beschreibung | *Description*	Länge | *Length*
65304	Toslink M/Toslink M G+ 0100 1,0m	1000 ± 30 mm
65305	Toslink M/Toslink M G+ 0200 2,0m	2000 ± 30 mm
65306	Toslink M/Toslink M G+ 0300 3,0m	3000 ± 30 mm
65307	Toslink M/Toslink M G+ 0500 5,0m	5000 ± 50 mm
65308	Toslink M/Toslink M G+ 1000 10,0m	1000 ± 100 mm

TOSLINK-Kabel

- TOSLINK-Kabel zur Audioübertragung von Fernsehern, Spielekonsolen oder Blu-ray-Playern an HiFi-Geräte wie SoundBar, Verstärker oder Stereoanlage
- Als optisches Audiokabel auf Glasfaserbasis ist das Kabel immun gegen elektrische Störeinflüsse - anders als herkömmliche Kupferkabel
- Mit 1 m hat das S/PDIF-Kabel die passende Länge, um Fernseher und HiFi-Anlage komfortabel miteinander zu verbinden
- Flexibles Premium-Kabel mit schlanken Metallsteckern, Knickschutz und farblich abgestimmtem Textilkabel
- Der geflochtene Textilmantel sorgt für eine angenehme Haptik und ist schonend auf sensiblen Oberflächen
- Das Kabel überbrückt auch große Distanzen störungsfrei und verlustfrei
- Vergoldete Stecker beugen Korrosion vor und sind besonders langlebig

Anschlüsse:	2x Toslink-Stecker
Material Gehäuse:	Aluminium
Material Kontakte:	vergoldet
Material Innenleiter:	GfK (Glasfaserverstärkter Kunststoff)
Außenmantel:	Ø 6.5 ± 0.15 mm

TOSLINK Cable

- *TOSLINK cable for audio transmission from TVs, game consoles or Blu-ray players to hi-fi equipment such as a SoundBar, amplifier or stereo system*
- *As an optical, glass fibre audio cable, the cable is immune to electrical interference - unlike conventional copper cables*
- *With 1 m, the S/PDIF cable is the right length to easily connect a TV set and a hi-fi system with each other*
- *Flexible premium cable with slim metal plugs, bend protection and colour-matched textile cable*
- *The braided textile sheath provides a pleasant feel and is gentle on sensitive surfaces*
- *The cable bridges even long distances without interference or losses*
- *The gold-plated plugs prevent corrosion and are especially durable*

Connection:	*2x Toslink male*
Material housing:	*Aluminium*
Material contact:	*gold-plated*
Material inner conductor:	*FRP (fibreglass-reinforced plastic)*
Cable sheath:	*Ø 6.5 ± 0.15 mm*

Änderungen			Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	16.01.2024	ir	Toslink M/Toslink M G+ XXXX 1x,xm	
		gepr.:	16.01.2024	TP		
		Norm:			Zeichnungs-Nr.:	von
		Änderungen vorbehalten / Subject to change			65304ff	