



- ATX 3.1 ready, native PCIe 5.1 dual-color 16-pin cable
- Supports NVIDIA® GeForce RTX™ 40 Series graphics cards
- Full modular design, Flat cables
- 80 Plus Gold certified for high efficiency
- Active PFC design, Industrial level protection with OVP, OCP, OPP, OTP, SCP, UVP
- 120mm Fluid Dynamic Bearing Fan
- LLC Full Bridge Topology with DC-DC module design

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (full modular)
Fan Bearing	Fluid Dynamic Bearing
Power Watt	750W
Power Excursion	1500W (*up to 200% of the PSU's rated power for 100µs)
Input Voltage	100~240 VAC
Input Frequency	47-63Hz
Connector	4-Pin PWM/DC
ATX (24 pin)	1
EPS (4+4 PIN)	2
Fan Size	120 mm
PCI-E 5.0 (16 pin)	1 (450W)
Dimension	140 x 150 x 86 mm
PCI-E (6+2 pin)	3
PFC Type	Active PFC
SATA (15 pin)	8
Protection	OCP / OVP / OPP / OTP / SCP / UVP
MOLEX (4 pin)	4
FDD (4 pin)	1

MAG A750GL PCIE5

AC INPUT	100-240~, 10A , 47-63Hz				
DC OUTPUT	+5V	+3.3V	+12V	-12V	+5Vsb
	20A	20A	62A	0.3A	2.5A
TOTAL POWER	110W	744W	3.6W	12.5W	
	750W				



POWER - SUPPLY
MAG A750GL PCIE5

CONNECTOR						
ATX	EPS	PCI-E 5.0	PCI-E	SATA	PERIPHERAL	FDD
1	2	1	3	8	4	1