

Specs

Wide-Angle Camera

Max. Resolution and Frame Rate	4K30fps
Field of View	110° HFOV
Digital Zoom	3x
CMOS Pixel	48MP
CMOS Sensor Size	1/1.3"

Telephoto Gimbal Camera

Max. Resolution and Frame Rate	4K30fps
Field of View	40° HFOV
Digital Zoom	3x
CMOS Pixel	48MP
CMOS Sensor Size	1/2.8"
Max. Pan-Tilt Range	Pan: +/- 35° Tilt: +/- 20°

Video

Video Coding	H.265, H.264 SVC, H.264 High profile, H.264 AVC
--------------	---

Audio

Microphone	14-Microphone Array
Pickup Range	33ft
Speakers	1

Max. Speaker Output Power	25W
Rated Speaker Power	20W

Network and Connection

LAN	10/100/1000 Mbps Ethernet
Wi-Fi	2.4 GHz, 5 GHz
Network Protocol	IPv4, IPv6
Bluetooth	Bluetooth 5.1

Ports

HDMI Input	1
HDMI Output	2
USB-A	USB-A 2.0, USB-A 3.0
USB-C	USB-C 3.0
Power	DC Port 12V/7A
Ethernet	Gigabit Ethernet
Security Slot	1

Basics & Environment

Dimensions (W x H x D)	685x76x85mm (27x3x3.3in)
Weight	2.27kg (80oz)
Operating temperature	32°F–104°F (0°C-40°C)
Storage temperature	-40°F to 158°F (-40°C to 70°C)
Humidity	<90%