

Be Your Window To The World

Der MSI PRO MP275QDE WQHD-Monitor mit HDMI und DisplayPort-Schnittstellen ist durch das IPS-Panel für beste Bild- und Farbqualität optimiert. Er wurde für die professionelle Arbeit in den Bereichen Programmierung, Codierung und Website-Design entwickelt. Er zeigt nicht nur jede Zeile und jedes Detail für Ihre Projekte klar und deutlich, sondern mit ihm lässt Sie auch reibungsloseste Streaming- und Videoerlebnisse genießen.



Picture and logos

SELLING POINTS

- Perfekte Bildschirmgröße von 27 Zoll mit WQHD (1440p) Auflösung für den Programmier-, Coding- und Webdesign-Arbeitsbereich.
- Das TÜV-zertifizierte Display gewährleistet den Schutz und die Gesundheit der Sehkraft.
- MSI EyesErgo-Technologie mit Anti-Flimmer-Technologie hilft, Augenbelastungen und Ermüdung vorzubeugen.
- Die Bildwiederholfrequenz von 100 Hz sorgt für ein besseres Seherlebnis mit flimmerfreien Bildern.
- MSI Eye-Q Check hilft dabei, die eigenen Augen zu überprüfen und erinnert daran, eine Pause einzulegen, wenn der Monitor längere Zeit verwendet wird.
- Vielseitigkeit über verschiedene Geräte hinweg, indem mehrere Eingangsquellen wie HDMI™- und DP-Anschlüsse genutzt werden können.
- Praktisches und abnehmbares Kabelmanagement-Design.
- Standardmäßig VESA-montierbar.
- Zwei eingebaute Lautsprecher.



1. 1x Stromanschluss
2. 1x HDMI™ (2.0b)
3. 1x DP (1.2a)
4. 1x HDMI™ (2.0b)
5. 1x Kopfhörerausgang
6. 1x Kensington Lock
7. 1x 5-Wege Navigation



SPECIFICATION

Model	SKU Number	0
	Entity MKT Name	PRO MP275Q
	Part No	9S6-3PC3CM-029
	Color	ID1/Black-Black
	MKT Name	PRO MP275Q
	MKT Spec	PRO MP275Q
	Model	3PC3
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	596.736 (H) x 335.664 (V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	2560x1440 (WQHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48 ~ 100Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1300:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	71.04~186.3 KHz(H) / 48~180 Hz(V)
	Refresh Rate	100HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	87%/81%
	NTSC (CIE1931 area percentage/overlap)	74%/72%
	sRGB (CIE1976 area percentage/overlap)	100%/95%
	sRGB (CIE1931 area percentage/overlap)	105%/95%
	Adobe RGB (CIE1976 area percentage/overlap)	85%/84%
	Adobe RGB (CIE1931 area percentage/overlap)	77%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	79%/79%
	DCI-P3 (CIE1931 area percentage/overlap)	77%/77%
	Rec.709 (CIE1976 area percentage/overlap)	100%/95%
	Rec.709 (CIE1931 area percentage/overlap)	105%/95%
	Rec.2020 (CIE1976 area percentage/overlap)	58%/58%
	Rec.2020 (CIE1931 area percentage/overlap)	55%/55%
	Surface Treatment	Anti-glare
	Display Colors	16.7M
	Color bit	10 bits (8 bits + FRC)
Schnittstellen	Headphone-out	1
	Card reader	N/A
	Lock type	Kensington Lock
	Speaker	2
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Garantie	Warranty	36M
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Annual Energy Consumption (KWh)	38
	Standby-mode Power Consumption (W)	0.5W
	Off-mode Power Consumption (W)	0.3W
	Energy Efficiency Rating	F
	Power Cord Type	C13

Zubehör	DisplayPort Cable	N/A
	HDMI Cable	1
	DVI Cable	N/A
	USB Type A to Type B Cable	N/A
	USB Type C to Type A Cable	N/A
	USB Type C to Type C Cable	N/A
	Thunderbolt Cable	N/A
	VGA Cable	N/A
	3.5mm audio Cable	N/A
	3.5mm combo audio Cable	N/A
	3.5mm Mic Cable	N/A
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
	Mouse Bungee Unit	0
	Switch Case	0
	Portable Screen Protection Case	0
	Monitor Hood	0
	Speaker (Accessories)	0
	VESA Screw	0
Schnittstellen (Vorne)	Card Reader	N/A
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Abmessungen & Gewicht (Product)	Product Dimension with Stand (WxDxH) (mm)	614.0 x 207.2 x 456.7
	Product Dimension without Stand (WxDxH) (mm)	614.0 x 55.9 x 361.1
	Stand Dimension (WxDxH) (mm)	227.8 x 207.2 x 146.3
	Weight (Net kg)	4.1
	Weight Without Stand (kg)	3.66
Abmessungen & Gewicht (Verpackung)	Inside Carton Dimension (WxDxH) (cm)	68.8 x 12.8 x 44.8
	Outer Carton Dimension (WxDxH) (cm)	70.8 x 14.6 x 48
	Weight (Gross kg)	5.54
Barcode Info	EAN	4711377153317
	UPC	824142342138
	UCC14	10824142342135
Schnittstellen (Rückseite)	Lock type	Kensington Lock
Abmessungen & Gewicht	Inside Carton Dimension (WxDxH) (inch)	27.09 x 5.04 x 17.64
	Weight (Net kg)	4.1
	Weight (Gross kg)	5.54
Produktmaße mit Standfuß	Product Dimension with Stand (WxDxH) (mm)	614.0 x 207.2 x 456.7
	Product Dimension with Stand (WxDxH) (inch)	24.17 x 8.16 x 17.98
Gewicht	Weight Without Stand (kg)	3.66
Verpackung	Outer Carton Dimension (WxDxH) (inch)	27.87 x 5.75 x 18.9