

«PeakTech® P 3441» TrueRMS digital multimeter ~ 60.000 Counts ~ 1000V AC/DC



€129.90

Prices excl. VAT plus shipping costs and possibly lower value surcharge

Product number: P 3441

GTIN/EAN: 4250569403651

Description

The PeakTech 3441 is a digital multimeter for heavy-duty use in heavy-duty design with a variety of useful measurement functions. The measurement display of the device can be switched between a 6,000-digit LCD and a high-resolution 60,000-digit LCD display, where all measurements being recorded as true rms values. In addition to the extensive measurement functions for current, voltage, capacitance, resistance and much more, this new development has a 4-20 mA% current loop measurement, a low-pass filter and an auto-hold function. During development, special emphasis was placed on user protection through the shock and impact-resistant housing and the high overvoltage category. Due to the extensive measurement functions and the intuitive operation, this device is ideally suited for every electronics engineer, technician and engineer who attach great importance to a precise, indestructible and technically powerful multimeter.

Technical features

- True RMS voltage up to 1000 V and current up to 10 A AC / DC
- LCD display with 6,000 digits switchable to 60,000 digits
- Resistance measurement, continuity tester and diode test
- Frequency measurement up to 10 MHz and Hz / duty function
- Capacitance measurement function up to 6 mF
- Temperature measurement function up to 760 °C

PeakTech Prüf- und Messtechnik GmbH
Gerstenstieg 4
DE-22926 Ahrensburg

www.peaktech.de

- Relative value, 4 ~ 20 mA% and low-pass filter measurement functions
- Data hold function, automatic and manual range selection
- Maximum value and minimum value function as well as peak function
- Safety: TÜV / GS, EN 61010-1, CAT III 1000V / CAT IV 600V
- Accessories: bag, test leads, temperature sensor and adapter, batteries and manual

Specifications

Basic Accuracy DC: +/- 0,9%

Battery: 1,5V AAA

Capacitance max.: 6 mF

Digital counts: 60.000

Display Type: LCD

GS - Tested safety: ■

OHM resolution min.: 0,01 Ω

Over voltage category: CAT III 1000 V, CAT IV 600 V

Range selection: Auto

True RMS: ■

V AC resolution min.: 0,01 mV

V DC Resolution min.: 0,01 mV

V DC max.: 1000V

A AC max.: 10A

Hz max.: 10 MHz

OHM max.: 60 M Ω

Temp. max.: 760 °C

Temp. min.: -50 °C

mA DC max.: 600mA

mV DC max.: 600 mV

μ A DC max.: 6000 μ A

V AC max.: 1000V

mV AC max.: 600 mV

A DC max.: 10A

mA AC max.: 600 mA



µA AC max.: 6000 µA