

APC Smart-UPS SMT

Tower Technical Specifications



	SMT750IC	SMT1000IC	SMT1500IC	SMT2200IC	SMT3000IC
Output					
Power Capacity	500 W/750 VA	700W / 1000VA	1000W / 1500VA	1980 W/2200 VA	2700 W/3000 VA
Nominal output voltage	230 V (configurable to 220 or 240 V nominal)				
Output frequency	47 - 53 Hz f or 50 Hz nominal; 57 – 63 Hz f or 60 Hz nominal				
Waveform type	Sine wave				
Output connections (NEMA)	(6) IEC320 C13	(8) IEC 320 C13		(8) IEC320 C13, (1) IEC320 C19	
Switched outlet groups	-	1			
Input					
Nominal input voltage	230V				
Input voltage range for main operations (Max adjustable)	160 – 286V (150 – 300V)				
Input frequency	50/60 Hz +/-3 Hz (auto sensing)				
Input connection	IEC320 C14			IEC320 C20, Schuko CEE7/EU1-16), British BS1363A	
Batteries and runtime					
Battery type	Maintenance-free sealed lead-acid battery with suspended electrolyte; leak proof				
Replacement battery	RBC48	RBC6	RBC7	RBC55	
Runtime estimates					
200W	:22	:45	1:24	2:17	2:29
500W	:05	:10	:23	:51	:55
700W	-	:06	:12	:34	:37
1000W	-	-	:07	:21	:23
1400W	-	-	-	:13	:14
1600W	-	-	-	:10	:12
Full load	:05	:06	:07	:07	:06
Communications and management					
APC SmartConnect Enabled	Yes				
Interface ports	Serial (RJ45), USB, and SmartSlot				
Control panel and audible alarms	Alpha-numeric LCD display with LED status indicators; alarm on battery, distinctive low battery alarm and configurable delays				
Emergency power off (EPO)	Optional			Yes	
Physical					
Maximum height (millimeter)	161	219	219	435	435
Maximum width (millimeter)	138	171	171	197	197
Maximum depth (millimeter)	363	439	439	54.4	54.4
Net weight (kilograms)	13.18	19.5	22.7	48.80	52.50
Conformance					
Regulatory	RCM, CE, EN62040-1, EN62040-2, EAC, VDE				

Life Is On

APC
by Schneider Electric