

P/N: TG56-2

Copyright

© 2023, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: TG56-2
 Commit: 92795
 Language: en-US
 Modified: 2023-07-13
 Formatted: 2023-07-13

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
Part number	TG56-2
Part name	30:1 Spot IR Thermometer
<p>The FLIR TG56-2 Spot IR Thermometer provides non-contact surface temperature readings so you can quickly and easily take measurements in places that are out of reach. Providing a distance-to-spot ratio of up to 30:1, the FLIR TG56-2 can measure small targets from a safe distance. Designed for those who require very high temperature measurements, TG56-2 can measure a maximum IR temperature of 1300°C (2372°F). It is also supplied with a Type K thermocouple for contact temperature readings. The FLIR TG56-2 has a color screen that makes it easy to navigate and select settings, plus adds visibility and efficiency to the advanced feature set. The FLIR TG56-2 is your go-to, pocket-sized device for efficient temperature measurement.</p>	
<p>Measure high and low:</p> <ul style="list-style-type: none"> • Easily take measurements in hard-to-reach spots at a distance. • Take non-contact surface temperature measurements, up to 1300°C, with an infrared sensor. • 30:1 spot ratio to measure small targets from a safe distance. • Easily identify measurement locations with built-in laser targeting. 	
<p>Simple to use:</p> <ul style="list-style-type: none"> • Color display, easy to navigate. • Graphical menu structure allows easy access to settings. • Easy emissivity selection with predetermined levels and custom adjustment. • Visual high and low alarms. 	
<p>Convenient and rugged design:</p> <ul style="list-style-type: none"> • Portable, compact size. • Rugged, industrial design that can withstand a 1 m drop. • Bright worklight to help you see your target in poor lighting conditions. 	
Spot infrared (IR) thermometer	
IR temperature range	-30°C to +1300°C (-22°F to +2372°F)
Basic accuracy	0°C to 100°C (32°F to 212°F): ±1.0°C (±1.8°F)
Emissivity	0.01 to 1.00 with 5 presets
Distance to spot	30:1
Measurement resolution	0.1°C (0.1°F)
IR temperature response time	250 ms
Spectral response	8 μm to 14 μm



FLIR TG56-2: 30:1 Spot IR Thermometer with Type K Thermocouple

P/N: TG56-2

© 2023, FLIR Systems, Inc.

#TG56-2; r. 92795; en-US

Spot infrared (IR) thermometer	
Max/Min	Min/Max/Avg/Dif Avg is from last 20 readings
Alarms	High/low alarms with programmable set points
Alarm alert	HI or LO will flash on the display
Included Type K Thermocouple Probe Range	-30°C to 260°C (-22°F to 500°F)
Input Type	K
Input Basic Accuracy	±1°C (±1.8°F) or 1% (whichever is greater)
Input Range	-30°C to 650°C (-22°F to 1202°F)
Laser	
Laser type	Single class II laser (red; visible light)
Laser power	≤ 1 mW, Class II
Laser alignment	Single point laser to upper edge of measurement
Power source	
Battery	9V alkaline battery (included)
Continuous Run Time	8 hours maximum continuous temperature measurements
Auto Power Off	5 or 15 seconds (selectable)
Battery documents	For documents like MSDS and UN38.3 test reports/summaries, see: https://support.flir.com/resources/msds
General	
Display	1.57" Color EBTN
Datalogging	Manual and automatic data logger
Memory	2 × 99 sets data storage
Scanning mode	Yes
Compatibility	Pipe Clamp Probe
Warranty	Limited 3-Year Warranty https://www.flir.com/testwarranty
Drop test	1 m (3.2 ft.)
IP rating	IP20
Worklight	Yes
Certifications	CE, UKCA, RCM, WEEE and FDA
Declaration of conformity	See: https://support.flir.com/resources/DoC
Physical data	
Weight	310 g (10.9 oz.)
Dimensions (L × W × H)	192 mm × 125 mm × 64 mm (7.5 in × 4.9 in × 2.5 in)
Shipping information	
Packaging type	Retail gift box
Packaging contents	<ul style="list-style-type: none">• Spot IR Thermometer• 9V battery• Quick Start Guide• Storage Pouch• Thermocouple



FLIR TG56–2: 30:1 Spot IR Thermometer with Type K Thermocouple

P/N: TG56-2

© 2023, FLIR Systems, Inc.

#TG56-2; r. 92795; en-US

Shipping information	
Packaging weight:	0.750 kg (1.65 lb.)
Packaging dimensions (L x W x H)	28.5 cm x 15 cm x 7.5 cm (11.2 in. x 5.9 in. x 2.95 in.)
UPC	793950402566
EAN	0793950402566
Country of origin	China
Tariff code / ECCN	9025198060 / 3A992a

Technical support	
Website	http://support.flir.com

Supplies & accessories:

- TA60; Thermocouple probe with adapter

