

ULTRASHARP MONITOR

DELL ULTRASHARP 43 4K USB-C HUB MONITOR – U4323QE

DELL ULTRASHARP 43 4K USB-C HUB MONITOR – U4323QE TECHNICAL SPECIFICATION

DIAGONAL VIEWING SIZE	107.95 cm 42.51 inches
PRESET DISPLAY AREA (H X V)	941.184 mm x 529.416 mm 37.05" x 20.84"
MAXIMUM PRESET RESOLUTION	3840 x 2160 @ 60Hz
PANEL TYPE	IPS Technology
DISPLAY SCREEN COATING	Anti-glare treatment of the front polarizer (3H) hard coating
VIEWING ANGLE	178° vertical / 178° horizontal
PIXEL PITCH	0.2451 mm x 0.2451 mm
PIXEL PER INCH (PPI)	103.6
CONTRAST RATIO	1000 to 1 (typical)
ASPECT RATIO	16:9
BACKLIGHT TECHNOLOGY	LED
BRIGHTNESS	350 cd/m ² (typical)
COLOR GAMUT	95% sRGB, 1.07 billion colors
RESPONSE TIME	5 ms gray to gray in Fast mode 8 ms gray to gray in Normal mode
HDR READY	No
CONNECTIVITY	• 2 x DP 1.4 • 2 x HDMI 2.1 (TMDS)¹ • 1 x USB-C (DP14 HB3 (2lane)/ HBR2 (4 Lane), Power Delivery upto 90W, 2/4 lane switching), USB 3.2 Gen 2 10Gbps upstream • 3 x USB-C (USB 3.2 Gen2, 10Gbps KVM) Upstream port, Data Only • 3 x super speed USB-A (USB 3.2 Gen2 10Gbps) downstream ports • 1 x super speed USB A (USB 3.2 Gen2 10Gbps) with B.C 1.2 • 1 x USB C (USB 3.2 Gen2 10 Gbps, Up to 15W charging) downstream Quick access port • 1 x Analog 2.0 audio line out (3.5mm jack) • 1 x RJ45 Port (PXE boot, MAC address pass thru, WoL, 1Gbps) Quick Access port
ADJUSTABILITY	Height adjustable (60mm) Tilt (-5° to 10°) Swivel (-20° to 20°) Pivot (NA)
PBP / PIP	PbP (Yes) PiP (Yes)
KEYBOARD, VIDEO AND MOUSE (KVM)	Yes, KVM and Auto KVM
DAISY CHAIN AVAILABILITY	Yes - iMST (Internal) for 4 unique FHD inputs from 1 PC
AUDIO OUTPUT	1 x Audio line-out ²
BUILT-IN SPEAKER	Yes - 2 x 8W
DELL DISPLAY MANAGER COMPATIBILITY	Yes, Easy Arrange, Other key features
SPECIFICATIONS - SERVICE / SUPPORT DETAILS	3-Year Advanced Exchange Service and Premium Panel Exchange
HEIGHT WITH STAND (COMPRESSED ~ EXTENDED)	595.20 mm ~ 655.20 mm (23.43" ~ 25.80")
WIDTH WITH STAND	967.21 mm (38.08")
DEPTH WITH STAND	256.40 mm (10.09")
HEIGHT WITHOUT STAND	560.50 mm (22.07")
WIDTH WITHOUT STAND	967.21 mm (38.08")
DEPTH WITHOUT STAND	64.08 mm (2.52 in)

1 Not supporting the HDMI 2.1 optional specification, including HDMI Ethernet Channel (HEC), Audio Return Channel (ARC), standard for 3D format and resolutions, standard for 4K digital cinema resolution, HDR, Fixed Rate Link(FRL), Enhanced audio return channel (eARC), Variable Refresh Rate (VRR), Quick Media Switching (QMS), Quick Frame Transport (QFT), Auto Low Latency Mode (ALLM), Display Stream Compression (DSC), and Source-Based Tone Mapping (SBTM).

2 Connect Speakers. Headphone use is not supported for the audio line out connector.

ULTRASHARP MONITOR

DELL ULTRASHARP 43 4K USB-C HUB MONITOR – U4323QE

DELL ULTRASHARP 43 4K USB-C HUB MONITOR – U4323QE TECHNICAL SPECIFICATION

WEIGHT (PANEL ONLY - FOR VESA MOUNT)	13.16 kg (29.01 lb)
WEIGHT (WITH STAND ASSEMBLY AND CABLES)	18.55 kg (40.90 lb)
WEIGHT (WITH PACKAGING)	25.23 kg (55.62 lb)
SECURITY	Security lock slot (cable lock sold separately) Anti-theft stand lock slot (to lock stand to monitor using screw)
COMPLIANT STANDARDS	- ENERGY STAR® Certified Monitor - EPEAT® Gold registered where applicable - RoHS Compliant - BFR/PVC Free (Halogen-free) (excluding external cables) - Arsenic-Free glass and Mercury-Free for the panel only
FLAT PANEL MOUNT INTERFACE	VESA mounting holes (100 mm x 100 mm and 200 mm x 200 mm - behind attached VESA Cover)
TEMPERATURE RANGE	Operating: 0°C to 40°C (32°F to 104°F) Non-operating: -20°C to 60°C (-4°F to 140°F)
HUMIDITY RANGE	Operating: 10% to 80% (non-condensing) Non-Operating: 5% to 90% (non-condensing) - Storage and Shipping
ALTITUDE	Operating: 5000 m (16404 ft) max Non-Operating: 12192 m (40000 ft) max
VOLTAGE REQUIRED	100 VAC to 240 VAC / 50 Hz or 60 Hz + 3 Hz / 2.6 A (max)
POWER CONSUMPTION NORMAL OPERATION	0.3 W (Off Mode) 0.3 W (Standby Mode) 52.1 W (On Mode) 250 W (Max)
WHAT'S INCLUDED	Monitor, Stand Riser, Stand Base 1 x Power cable 1 x Type-C Gen 2 PD 3.0 (C-C cable) - 1 m 1 x DP Cable (DP to DP) - 1.8 m 1 x Type-C Gen 2 - 1.8 m (Type A to Type C) 1 x HDMI Premium High Speed (HDMI-HDMI) - 1.8 m Quick setup guide Safety, Environmental and Regulatory Information

PORTS AND SLOTS



- | | | |
|---|--|--|
| 1 Security lock slot (based on Kensington Security Slot™) | 7 USB-C 1 upstream port (Video + Data) | 13 RJ45 connector |
| 2 Power connector | 8 Audio line-out port ¹ | 14 Stand lock |
| 3 HDMI 1 port | 9 USB-C 2 upstream port (data only) | 15 Quick access USB port 2 - USB-C data port |
| 4 HDMI 2 port | 10 USB-C 3 upstream port (data only) | 16 Quick access USB port 2 - USB-A Super speed 10Gbps (USB 3.2 Gen2) |
| 5 DisplayPort in 1 | 11 USB-C 4 upstream port (data only) | 17 Speakers (2 x 8W) |
| 6 DisplayPort in 2 | 12 Super speed USB 10Gbps (USB 3.2 Gen2) (3) | |

¹ Connect Speakers. Headphone use is not supported for the audio line out connector.