




USB Type-C 6-Port Hub

Bridge Devices, Expand Connections

UH6120C



1× HDMI
4K@60Hz



1× PD
100W



1× RJ45
1 Gbps



USB-C/2× USB-A
5 Gbps

Highlights



Plug & Play
For Various Operating Systems[‡]



Convenient & Stylish
Self-Storage for Connector

Bridge Devices, Expand Connections




HDMI
Ultra High-Definition
Media Display



RJ45 GE
Stable Gigabit
Connection



PD 3.0
Powerful 100W
Fast Charging



USB 3.0
5 Gbps SuperSpeed
Data Transfer



**Scratch
Resistant**
Aluminum Alloy Case



**Durable
Design**
Braided Cable

Specifications

Hardware

- **Interface:**
 - 1× PD 100W Charging
 - 1× USB Type-C 5Gbps
 - 2× USB Type-A 5Gbps
 - 1× HDMI 4K@60Hz
 - 1× RJ45 1Gbps
- **Connector:**
 - 1× USB Type-C
- **PD Input:**
 - 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A
- **USB-C Connector Input:**
 - 5V/3A

Physical

- **Dimension (W×D×H):**
 - 4.65 × 1.69 × 0.56 in (118.2 × 43 × 14.3 mm)
- **Case:**
 - Aluminum Alloy Case
- **Cable:**
 - 180mm Braided Cable
- **Package Contents:**
 - 1× UH6120C
 - 1× Quick Installation Guide

Others

- **Supported Systems:**
 - Mac OS X 10.9 and later, Windows (7 and later), Linux OS, iPad OS, iOS, Android, Chrome OS, and Nintendo OS
- **Plug & Play:**
 - USB-C PD port, USB-C port, HDMI port, USB-A ports, Gigabit Ethernet port.*
The gigabit Ethernet port may require installing a driver for compatibility with certain older operating systems. Please visit our official website at www.tp-link.com to download the necessary driver for these systems:
 - Windows 7/8
 - Mac OS X 10.9 to 10.15
- **Certi ication:** CE, RoHS, HDMI, BSMI
- **Environment:**
 - Operating Temperature: 0°C~40°C (32°F~104°F)
 - Operating Humidity: 10%~90% non-condensing
 - Storage Humidity: 5%~90% non-condensing



For more information, please visit
https://www.tp-link.com/products/details/?model=UH6120C_V1
or scan the QR code left

Specifications are subject to change without notice. All the brands and product names are trademarks or registered trademarks of their respective holders.
*Port transmission specifications are the testing result conducted by TP-Link laboratory. Actual transfer rate is not guaranteed and will vary as a results of device conditions and environmental factors.
*Plug and Play for Mac OS X El Capitan Version 10.11.6 and later, Windows 11/10/8.1, Linux OS, iPad OS, iOS, Android, Chrome OS, and Nintendo OS. More OS versions will be supported soon.

[§]To ensure compatibility, you may need to update the hub's drivers after an OS update. You can find our latest drivers in the download center at tp-link.com/en/download-center.
©2024 TP-Link