

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Spray adhesive Graphic Mount

Article number: 100063, 100063/1

UFI: 9R70-Q0W1-V008-CFTW

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU21 Consumer uses: Private households / general public / consumers

Application of the substance / the mixture Adhesives

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Stanger Produktions- und Vertriebs GmbH & Co KG

Ferdinand-Porsche-Straße 2

D-32339 Espelkamp

Telefon: +49 5743-9307-0

Further information obtainable from:

Abteilung Produktsicherheit

info@stanger.de

1.4 Emergency telephone number:

+49-5743-9307-0

(Montag bis Freitag, 7:00 - 17:00 Uhr)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

GHS label elements

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS09

Signal word Danger

Hazard-determining components of labelling:

pentane

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

Trade name: Spray adhesive Graphic Mount

(Contd. of page 1)

hexane (containing < 5 % n-hexane (203-777-6))

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards**Results of PBT and vPvB assessment** Not applicable.**PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:**

Mixture of substances listed below with nonhazardous additions.

Active substance with propellant

Dangerous components:

CAS: 109-66-0 EINECS: 203-692-4	pentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	25-75%
CAS: 109-87-5 EINECS: 203-714-2 Reg.nr.: 01-2119664781-31-0000	dimethoxymethane Flam. Liq. 2, H225	<25%
CAS: 74-98-6 EINECS: 200-827-9	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	<20%
CAS: 75-28-5 EINECS: 200-857-2	isobutane Flam. Gas 1, H220; Press. Gas (Comp.), H280	<15%
CAS: 107-83-5 EINECS: 203-523-4	hexane (containing < 5 % n-hexane (203-777-6)) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥2.5-<10%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315	≥0.25-<2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

Trade name: Spray adhesive Graphic Mount

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

No special measures required.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 2 B

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:
109-66-0 pentane
WEL Long-term value: 1800 mg/m³, 600 ppm

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

Trade name: **Spray adhesive Graphic Mount**

(Contd. of page 3)

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection: Not required.**Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

Butyl rubber, BR

Nitrile rubber, NBR

For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Chloroprene rubber, CR

Eye protection: Not required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Aerosol
Colour:	Light yellow
Odour:	Mild

Change in condition

Initial boiling point and boiling range:	<0 °C Not applicable, as aerosol.
---	--------------------------------------

Flash point:	-97 °C
---------------------	--------

Ignition temperature:	235 °C
------------------------------	--------

Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
------------------------------	---

Explosion limits:

Lower:	1.4 Vol %
Upper:	10.9 Vol %

Vapour pressure at 20 °C:	8,300 hPa
----------------------------------	-----------

Density at 20 °C:	0.65 g/cm ³
--------------------------	------------------------

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

Trade name: Spray adhesive Graphic Mount

(Contd. of page 4)

Solubility in / Miscibility with**water:**

Not miscible or difficult to mix.

Organic solvents:

80.9 %

VOC (EC)

622.3 g/l

**Verordnung über die Lenkungsabgabe auf
flüchtigen organischen Verbindungen (Stand am
1. Januar 2009)**

VOCV (CH)

73.73 %

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	20 mg/l (rat)

Primary irritant effect:**Skin corrosion/irritation** Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.**Aspiration hazard**

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity**Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Remark:** Toxic for fish

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

Trade name: Spray adhesive Graphic Mount

(Contd. of page 5)

Additional ecological information:**General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

12.5 Results of PBT and vPvB assessment Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Smaller quantities can be disposed of with household waste.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number****ADR, IMDG, IATA**

UN1950

14.2 UN proper shipping name**ADR**UN1950 AEROSOLS, ENVIRONMENTALLY
HAZARDOUS**IMDG**

AEROSOLS, MARINE POLLUTANT

IATA

AEROSOLS, flammable

14.3 Transport hazard class(es)**ADR****Class**

2 5F Gases.

Label

2.1

IMDG**Class**

2.1

Label

2.1

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

Trade name: Spray adhesive Graphic Mount

(Contd. of page 6)

IATA

Class 2.1
Label 2.1

14.4 Packing group
ADR, IMDG, IATA Void

14.5 Environmental hazards: Product contains environmentally hazardous substances:
pentane
Marine pollutant: Yes
Special marking (ADR): Symbol (fish and tree)

14.6 Special precautions for user Warning: Gases.
Hazard identification number (Kemler code): -
EMS Number: F-D,S-U
Stowage Code SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear
of living quarters.
Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1
except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

14.7 Transport in bulk according to Annex II of
Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR
Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
Transport category 2
Tunnel restriction code D

IMDG
Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity

UN "Model Regulation": UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY
HAZARDOUS

*

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2020

Version number 2.8

Revision: 21.08.2020

Trade name: Spray adhesive Graphic Mount

(Contd. of page 7)

Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Abteilung Produktsicherheit**Contact:** Hr. Dr. Pohle**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - inhalation – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

GB