



中国认可
检验
INSPECTION
CNAS IB0071



NO.2622070107

SAFETY DATASHEET

Product Name: Li-ion Battery Pack NIU-48M13A0
46.8V 13Ah 608.4Wh

Effective Date: 2022-07-13

Compiler: He Xiaoshuang

Checker: Liu Lintian

Approver: Zhangxiangjin



Shanghai Institute of Chemical Industry Testing Co., Ltd.



Jiangsu Niu Electric Technology Co.,ltd

SAFETY DATA SHEET

Li-ion Battery Pack NIU-48M13A0 46.8V 13Ah 608.4Wh

SECTION1 PRODUCT AND COMPANY IDENTIFICATION

Product name: Li-ion Battery Pack NIU-48M13A0 46.8V 13Ah 608.4Wh
Company: Jiangsu Niu Electric Technology Co.,ltd
Address: No.387 Changting Road,West Taihu Science and Technology Industrial Park, Changzhou City, Jiangsu, 21300, P. R. China
Email: Zu.renzheng@niu.com
Fax: 86-519-68218077
Emergency Phone: 86-519-68218077
Recommend use of the chemical and restrictions on use: /

SDS Number: 2622070107
Effective Date: 2022-07-13

SECTION2 HAZARDS IDENTIFICATION

The product is outside of the scope of GHS system.

Main Hazards:

Fire or Explosion Hazards:

Lithium ion battery contains flammable liquid electrolyte that may vent, ignite and produce sparks when subjected to high temperatures (>150°C), when damaged or abused (e.g., mechanical damage or electrical overcharging). May burn rapidly with flare-burning effect. May ignite other batteries in close proximity.

Health Hazards:

Contact with the electrolyte of battery may be irritating to skin, eyes and mucous membranes. Fire will produce irritating, corrosive and/or toxic gases. Fumes may cause dizziness or suffocation.

SECTION3 INFORMATION ON INGREDIENTS

Product name: Li-ion Battery Pack NIU-48M13A0 46.8V 13Ah 608.4Wh

Ingredient	Concentration	CAS No.	EC No.
Cobalt lithium manganese nickel oxide	<35%	182442-95-1	/

Graphite	<25%	7782-42-5	231-955-3
Copper	<15%	7440-50-8	231-159-6
Aluminum	<10%	7429-90-5	231-072-3
Dimethyl carbonate	<8%	616-38-6	210-478-4
Ethylene carbonate	<5%	96-49-1	202-510-0
Lithium hexafluorophosphate	<5%	21324-40-3	244-334-7
Carbon black	<5%	1333-86-4	231-153-3
Carboxymethyl cellulose sodium salt	<2%	9004-32-4	618-378-6
Polyvinylidene fluoride	<2%	24937-79-9	607-458-6

SECTION4 FIRST-AID MEASURES

Skin Exposure:

If in contact with the internal materials of battery, remove the contaminated clothing, shoes and socks, immediately flush with plenty of water for at least 20 minutes. Call a physician.

Eye Exposure:

If in contact with the internal materials of battery, lift your eyelids immediately and rinse them with running water for more than 20 minutes. Call a physician.

Inhalation Exposure:

If the internal materials of battery are inhaled, immediately remove to fresh air. If breathing is difficult give oxygen. If not breathing, give artificial respiration. Call a physician.

Oral Exposure:

Do not induce vomiting if the internal materials of battery are swallowed. Call a physician immediately.

Most Important Symptoms/Effects, Acute and Delayed:

No data available.

Indication of Immediate Medical Attention and Special Treatment Needed, if Necessary:

No data available.

SECTION5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Suitable:Water spray or regular foam.

Specific Hazards Arising from the Chemical:

May decompose upon combustion to generate irritating, corrosive or toxic fumes. Fumes may cause dizziness or suffocation.

Special Protective Action for Fire-fighters:

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Fire-extinguishing work is done from the windward. Uninvolved persons should evacuate to a safe place.

SECTION6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Use personal protective equipment. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Entry to noninvolved personnel should be controlled around the leakage area by roping off. Remove all sources of ignition.

Environmental Precautions:

Avoid leakage getting into the earth, ditches or waters. Avoid directly releasing the washing waste-water into the environment.

Methods and Materials for Containment and Cleaning up:

If the electrolyte leaks, use soil, sand or other non-combustible materials to absorb. The leaked batteries and dirty adsorbents should be placed in metal containers.

SECTION7 HANDLING AND STORAGE**Precautions for Safe Handling:**

Operators should be trained and strictly abide by operating procedures. Wear appropriate protective clothing and safety gloves. Keep away from ignition sources, heat and flame. No smoking at working site. Handling is performed in a well ventilated place. Avoid disassembling the battery at will and reversing battery polarity within the battery assembly. The battery must be firmly packed in inner packaging so as to effectively prevent short circuits and short circuits caused by movement. If the electrolyte leaks, avoid directly contacting with eyes and skin. Avoid inhalation. Incompatibilities: Strong oxidizing agents, combustible materials and corrosives.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in a cool, dry, and well-ventilated area. Keep away from ignition sources, heat and flame. Incompatibilities: Strong oxidizing agents, combustible materials and corrosives. The battery must be firmly packed in inner packaging so as to effectively prevent short circuits and short circuits caused by movement. Storage place should be equipped with appropriate varieties and quantities of fire fighting equipment and leakage emergency treatment equipment.

SECTION8 EXPOSURE CONTROL/PPE**Control Parameters:**

GBZ 2.1-2019 Occupational Exposure Limits for Hazardous Agents in the Workplace - Part 1: Chemical Hazardous Agents:

Manganese and inorganic compounds, as MnO₂ PC-TWA 0.15mg/m³ Nickel metal and insoluble compounds PC-TWA 1mg/m³ (Remarks: G2B) (metal and alloy)

Cobalt and compounds, as Co PC-TWA 0.05mg/m³ PC-STEL 0.1mg/m³ (Remarks: G2B) Sensitization

Graphite dust: PC-TWA 4mg/m³ (total dust) 2mg/m³ (inhalable dust)

Copper: Copper dust PC-TWA 1mg/m³; Copper smoke PC-TWA 0.2mg/m³

Aluminum metal and aluminum alloy dust: PC-TWA 3mg/m³ (total dust)

Carbon black dust : PC-TWA 4mg/m³ (total dust)

ACGIH:

Graphite: TLV-TWA 2 mg/m³

Copper: TLV-TWA 1 mg(Cu)/m³, dust, mist TLV-TWA 0.2 mg(Cu)/m³, fume

Aluminum: TLV-TWA: 1 mg/m³

Carbon black: TLV-TWA: 3 mg/m³ (inhalable dust)

Appropriate Engineering Controls:

Mechanical exhaust required. Safety shower and eye bath.

Individual Protection Measures:**Eye/Face Protection:**

Wear chemical safety glasses if needed.

Skin Protection:

Hand Protection: Wear safety gloves.

Body Protection: Wear appropriate protective clothing.

Respiratory Protection:

Wear government approved respirator if needed.

Thermal Hazards:

No data available.

Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION9 PHYSICAL/CHEMICAL PROPERTIES**Appearance:** Black plastics cement and metal shell**Odor:** Odorless**pH Value:** 8-9**Solubility:** Partial soluble in water**Boiling Point,** No data available**Initial Boiling
Point and Boiling****Range:**
Melting >300°C**Point/Freezing****Point:****Flash Point** No data available**(Closed Cup):****Density/Relative** No data available**Density:****Kinematic** No data available**Viscosity:****Lower/Upper** No data available**Explosion****Limit/Flammabili****ty Limit:****Vapour Pressure:** No data available**Relative Vapor** No data available**Density:****Partition** No data available**Coefficient****N-Octanol/Water(****Log Value):****Autoignition** No data available**Temperature:****Decomposition** No data available**Temperature:****Particle** No data available**Characteristics:****Flammability** No data available**(Solid, Gas):****SECTION10 STABILITY AND REACTIVITY****Reactivity:**

No data available.

Chemical Stability:

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions:

No data available.

Conditions to Avoid:

Avoid misoperation, exposure to heat and open flame. Avoid mechanical or electrical abuse and overcharge.
Prevent short circuits and short circuits caused by movement.

Incompatible Materials:

Strong oxidizing agents, combustible materials and corrosives.

Hazardous Decomposition Products:

Carbon oxides, metal oxides, etc.

SECTION11 TOXICOLOGICAL INFORMATION

Acute Toxicity:

No data available.

Skin Corrosion/Irritation:

The electrolyte in the battery causes skin irritation.

Serious Eye Damage/Irritation:

The electrolyte in the battery causes eye irritation.

Respiratory Sensitization:

No data available.

Carcinogenicity:

No data available.

Skin Sensitization:

No data available.

Germ Cell Mutagenicity:

No data available.

Reproductive Toxicity:

No data available.

Specific Target Organ Toxicity -Single Exposure:

No data available.

Specific Target Organ Toxicity -Repeated Exposure:

No data available.

Aspiration Hazard:

No data available.

SECTION12 ECOLOGICAL INFORMATION

Toxicity:

No data available.

Persistence and Degradability:

No data available.

Bioaccumulative Potential:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects:

No data available.

SECTION13 DISPOSAL CONSIDERATION

Disposal Methods:

The disposal of discarded battery shall comply with the requirements of relevant laws, regulations, policies and standards such as the "Law of the People's Republic of China on the Prevention and Control of Environmental Pollution by Solid Waste" and "Technical Policy for the Prevention and Control of Waste Battery Pollution". Contact a licensed professional waste disposal service to dispose of wastes. Used battery being transported for disposal or reclamation should be carefully checked prior to shipment to ensure the integrity of each battery and its suitability for transport.

SECTION14 TRANSPORT INFORMATION

Lithium Battery
Pack Contained in
KQi3 MAX Electric
Scooter during
Transport:

The product has passed the test items of UN Model Regulations, Manual of Test and Criteria Section 38.3.

RID/ADR (2021
Edition) :

Proper Shipping Name: Battery powered vehicle
UN Number: UN3171
Hazard Label: Miscellaneous
Hazard Class: 9

According to 2.2.9.1.7 (g) of RID/ADR(2021 Edition), Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

IATA DGR (63rd
Edition) :

Proper Shipping Name: Battery powered vehicle
UN Number: UN3171
Hazard Label: Miscellaneous
Hazard Class: 9

According to 3.9.2.6.1(g) of IATA DGR (63rd Edition) , Manufacturers and subsequent distributors of cells or batteries manufactured after 30 June 2003 shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

IMO IMDG
Code(2020
Edition):

Proper Shipping Name: Battery powered vehicle
UN Number: UN3171
Hazard Label: Miscellaneous
Hazard Class: 9
EmS No. : F-A, S-I

According to 2.9.4.7 of IMO IMDG Code (2020 Edition) , Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

Lithium Battery
Packed with KQi3
MAX Electric
Scooter during
Transport:

The product has passed the test items of UN Model Regulations, Manual of Test and Criteria Section 38.3.

RID/ADR(2021 Edition):	Proper Shipping Name: Lithium ion batteries packed with equipment UN Number: UN3481 Hazard Class: 9 According to 2.2.9.1.7 (g) of RID/ADR(2021 Edition), Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.
IATA DGR (63rd Edition) :	Proper Shipping Name: Lithium ion batteries packed with equipment UN Number: UN3481 Hazard Class: 9 The product shall meet the General Requirements and section I of Packaging Instruction 966. According to 3.9.2.6.1(g) of IATA DGR (63 rd Edition) , Manufacturers and subsequent distributors of cells or batteries manufactured after 30 June 2003 shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.
IMO IMDG Code (2020 Edition) :	Proper Shipping Name: Lithium ion batteries packed with equipment UN Number: UN3481 Hazard Class: 9 EmS No: F-A, S-1 According to 2.9.4.7 of IMDG Code(2020 Edition), Manufacturers and subsequent distributors of cells or batteries manufactured shall make available the test summary as specified in the Manual of Tests and Criteria, Part III, sub-section 38.3, paragraph 38.3.5.

SECTION15 REGULATORY INFORMATION

Domestic Regulations:

Lithium Battery Pack Contained in the Equipment during Transport:

Regulations Concerning Road Transportation of Dangerous Goods (JT/T 617-2018) :

UN Number: 3171 Name and Description: Battery powered vehicle

The product is not subject to JT/T 617-2018 according to special provision 240.

List of Dangerous Goods (GB 12268-2012) :

UN Number: 3171 Shipping Name: Battery powered vehicle

The product is not subject to GB 12268-2012 according to special provision 106.

List of Dangerous Goods by Rail (2009 Edition) :

The product is not subject to List of Dangerous Goods by Rail (2009).

Lithium Battery Packed with the Equipment during Transport:

Regulations Concerning Road Transportation of Dangerous Goods(JT/T 617-2018):

UN Number: UN3481 Name and Description: Lithiumion batteries packed with equipment

List of Dangerous Goods(GB 12268-2012):

UN Number: UN3481 Proper Shipping Name: Lithium ion batteries packed with equipment

List of Dangerous Goods by Rail (2009 Edition) :

Number: 91014 Name of Product: Lithium batteries packed with equipment

International Regulations:

Directive 2006/66/EC and 2013/56/EU:

The label, disposal and recycling of the battery shall meet the requirements of EU Directive 2006/66/EC and 2013/56/EU.

ICAO TI:

1. Unless be exempted according to ICAO TI, the lithium ion cell/batteries (UN 3480, PI 965) and lithium metal cell/batteries (UN 3090, PI 968) are forbidden for carriage on passenger aircraft.
2. Unless be approved according to ICAO TI, Lithium ion cells/batteries (UN 3480, PI 965) must be offered for transport at a state of charge (SoC) not exceeding 30% of their rated design capacity.
3. A shipper is not permitted to offer for transport more than one (1) package prepared according to Section II of PI 965 and PI 968 in any single consignment. Not more than one (1) package prepared in accordance with Section II of PI 965 and PI 968 may be placed into an overpack.
4. Packages prepared according to Section II of PI 965 and PI 968 must be offered to the operator separately from other cargo and must not be loaded into a unit load device (ULD) before being offered to the operator.

SECTION16 OTHER INFORMATION

Preparation Date:

2022-07-13

Preparation Department:

Shanghai Research Institute of Chemical Industry Testing Co., Ltd.
Tel (Fax) : +86-21-52815377/31765555

Revision:


0

Abbreviations and Acronyms:

CAS: Chemical Abstracts Service EC: European Commission ACGIH: American Conference of Governmental Industrial Hygienists PC-TWA: Permissible concentration-time weighted average TLV-TWA: Time weighted average threshold limit Sensitization: The substance may have allergenic effects G2B: Possibly carcinogenic to humans PC-STEL: Permissible concentration-short term exposure limit ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road RID: Regulations concerning the International Carriage of Dangerous Goods by Rail IMO IMDG CODE: International Maritime Organization International Maritime Code for Dangerous Goods EmS: Emergency schedule IATA DGR: International Air Transport Association Dangerous Goods Regulations EU: European Union ICAO TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air PI:Packaging Instruction

Other Information:

This SDS is only compiled for battery and based on the information such as ingredients provided by the applicant and our current knowledge. This SDS shall be used only as a guide. If the battery is used as a component in another product, the information in this SDS may not be applicable. The users of this SDS must make independent judgments on the correctness and completeness and then decide its suitability according to the actual situation. The users should take the relevant legal responsibilities for the consequences of use.



46.8 VDC 13 Ah (608.4 Wh)

LI-ION BATTERY PACK

131NR19/66-5 NIU-48M1340

54.6 V	≤80% RH	0°C-45°C	-15°C-60°C	0°C-40°C	30%-70%
Charging Voltage Tension de charge Ladegerät Tension de charge	Operating Humidity Humidité de fonctionnement Feuchtigkeit des Betriebes Humidità de funcionamento	Charging Temperature Température de charge Ladetemperatur Temperatura de carga	Operating Temperature Température de fonctionnement Betriebstemperatur Temperatura de funcionamiento	Storage Temperature Température de stockage Lagertemperatur Temperatura de almacenamiento	Storage Battery Level Niveau de stockage de la batterie de stockage Niveau de almacenamiento de la batería Nível de carga de la bateria

D1) The battery needs to be charged every 2 months. / La batterie doit être rechargée tous les 2 mois. / Die Batterie muss alle 2 Monate aufgeladen werden. / La batería debe cargarse cada 2 meses.

⚠ WARNING / AVERTISSEMENT / WARNUNG / ADVERTENCIA

- The battery should only be used and stored under recommended environment to ensure the service life.
- Using non-original fast charging device may cause battery leakage, swelling, smoke, and fire.
- Do not disassemble any part of the battery pack as this may result in electric shock, chemical leakage, swelling, smoke, and fire.
- The battery should be protected from piercing by sharp objects and dropping; piercing and dropping may result in electric shock, chemical leakage, swelling, smoke, and fire.
- Recycle or dispose of in accordance with local regulations.
- Warning - To reduce the risk of injury, user must read instruction manual.

Do Not Disassemble the Battery Pack! / Ne démontez pas le bloc-pile!
Zerlegen Sie das Batteriepack nicht! / No desarme la batería!

- La batterie ne doit être utilisée et stockée que dans un environnement recommandé afin d'assurer sa durée de vie.
- Utiliser un dispositif de charge non original peut entraîner une fuite de la batterie, une enflure, de la fumée et un incendie.
- Ne démontez aucune partie du bloc-pile, car cela pourrait entraîner un choc électrique, une fuite chimique, une enflure, de la fumée et un incendie.
- La batterie doit être protégée contre le percage par des objets tranchants et la chute. Le percage et la chute peuvent entraîner un choc électrique, une fuite chimique, une enflure, de la fumée et un incendie.
- Recycler ou éliminer conformément à la réglementation locale.
- AVERTISSEMENT - Pour réduire les risques de blessure, l'utilisateur doit lire le manuel d'instructions.

Manufacturer: Anpower New Electric Technology Co., Ltd.
Factory: Yancheng Elite New Energy Co., Ltd.

检验检测专用章
(13)